



TS20

Plate heat exchanger

Applications

General heating and cooling duties. Heating by means of steam.

Standard design

The plate heat exchanger consists of a pack of corrugated metal plates with portholes for the passage of the two fluids between which heat transfer will take place.

The plate pack is assembled between a fix frame plate and a movable pressure plate and compressed by tightening bolts. The plates are fitted with a gasket which seals the interplate channel and directs the fluids into alternate channels. The number of plates is determined by the flow rate, physical properties of the fluids, pressure drop and temperature program. The plate corrugations promote fluid turbulence and support the plates against differential pressure.

The plate and the pressure plate are suspended from an upper carrying bar and located by a lower guiding bar, both of which are fixed to a support column.

Connections are located in the frame plate or, if either or both fluids make more than a single pass within the unit, in the frame and pressure plates.

Typical capacities

Liquid flow rate

Up to 190 kg/s, depending on media, permitted pressure drop and temperature program.

Water heating by steam

2.5 - 15 MW at a steam condensation temperature of 150°C

2.5 - 9 MW at a steam condensation temperature of 120°C

Plate types

TS20M plates

Frame types

FM, FG and FS



TS20-MFG

Working principle

Channels are formed between the plates and the corner ports are arranged so that the two media flow through alternate channels. The heat is transferred through the plate between the channels, and complete counter-current flow is created for highest possible efficiency. The corrugation of the plates provides the passage between the plates, supports each plate against the adjacent one and enhances the turbulence, resulting in efficient heat transfer.

STANDARD MATERIALS

Frame plate

Mild steel, Epoxy painted

Nozzles

Carbon steel

Metal lined: Stainless steel, Titanium

Rubber lined: Nitrile, EPDM

Plates

Stainless steel Alloy 316 or Titanium

Gaskets

Nitrile, EPDM or HeatSealF™

TECHNICAL DATA

Pressure vessel codes, PED, ASME, pvcALS™


Mechanical design pressure (g) / temperature

FM	PED, pvcALS™	1.0 MPa / 180°C
FG	PED	1.6 MPa / 180°C *)
FG	ASME	150 psig / 350°F
FG	pvcALS™	1.6 MPa / 180°C
FS	PED	3.0 MPa / 160°C
FS	ASME	150 psig / 350°F

*) Frame FG also approved for 1.2 MPa / 200°C to allow use in steam systems without safety valves.


CONNECTIONS

FM	PED	Size 200 mm	DIN 2501, PN10, ASME Cl. 150
FM	pvcALS™	Size 200 mm	DIN 2501, PN10, ASME Cl. 150, JIS 10K
FG	PED	Size 200 mm	DIN 2501, PN16, ASME Cl. 150
FG	ASME	Size 8"	ASME Cl. 150
FG	pvcALS™	Size 200 mm	DIN 2501, PN16, ASME Cl. 150, JIS 10K
FS	PED	Size 200 mm	DIN 2501, PN25/PN40, ASME Cl. 300
FS	ASME	Size 8"	ASME Cl. 300/ASME Cl. 150



Flow principle of a plate heat exchanger

Dimensions



Measurements (mm)

Type	H	W	h
TS20-MFM	1405	740	360
TS20-MFG	1405	800	360
TS20-MFS	1435	800	390

The number of tightening bolts may vary depending on pressure rating.

Maximum heat transfer surface

85 m² (910 sq. ft)

Particulars required for quotation

- Flow rates or heat load
- Temperature program
- Physical properties of liquids in question (if not water)
- Desired working pressure
- Maximum permitted pressure drop
- Available steam pressure

How to contact Alfa Laval

Up-to-date Alfa Laval contact details for all countries are always available on our website at www.alfalaval.com

GIAFLEX

GIA-S d.o.o., Industrijska cesta 5, 1290 Grosuplje, Slovenija
 Telefon: +386 1 7865 300, Telefax: +386 1 7863 568,
info@gia.si, www.giaflex.com